

JUNGHEINRICH EFG 540K

Specifications

Identification	1.1	Manufacturer (short form)		
	1.2	Model		EFG 540k
	1.3	Drive		
	1.4	Manual, pedestrian, stand-on, seated, order picker operation		
	1.5	Load capacity/rated load	Q t	4
	1.6	Load centre distance	c mm	
	1.8	Load distance	x mm	
	1.9	wheelbase	y mm	1856
	Weights	2.1.1	Net weight incl. battery (see row 6.5)	kg
2.2		Axle load, w. load, front / rear	kg	9730 / 996
2.3		Axle load, w.o. load, front / rear	kg	3553 / 3173
Wheels / chassis	3.1	Tyres		
	3.2	Tyre size, at front	mm	250-15
	3.3	Tyre size, at rear	mm	
	3.5	Wheels, number front/rear (x = driven wheels)		
	3.6	Track width, front	b10 mm	1115
	3.7	Track width, rear	b11 mm	
	Basic dimensions	4.1	Tilt of mast/fork carriage forward/backward	α/β °
4.2		mast height (lowered)	h1 mm	2250
4.3		Free lift	h2 mm	
4.4		Lift	h3 mm	
4.5		Extended mast height	h4 mm	3675
4.7		Height of overhead guard	h6 mm	2365
4.8		Seat height/stand height	h7 mm	
4.12		Coupling height	h10 mm	
4.12.1		2nd coupling height	mm	
4.19		total length with fork length 1150 mm	l1 mm	3808
4.20		Length incl. back of forks	l2 mm	2658
4.21		Total width	b1/b2 mm	1340
4.22		fork dimensions	s/e/l mm	50 / 125 / 1150
4.23		Fork carriage ISO 2328, class/type A, B		
4.24		fork carriage width	b3 mm	
4.31		floor clearance with load under mast	m1 mm	136
4.32		Floor clearance centre wheelbase	m2 mm	
4.33	Aisle width for pallets 1000 x 1200 sideways	Ast mm	3965	
4.34	Aisle width for pallets 800 x 1200 lengthways	Ast mm	4165	
4.35	turning radius	Wa mm	2284	
4.36	Smallest pivot point distance	b13 mm	660	

Dimensions

